
SSD Status



Davis Collaboration Meeting – June 17, 2008 Howard Matis


The SSD




Acceptance: $-1.2 < \eta < 1.2$ $0 < \phi < 2\pi$

Silicon Arrangement

- \circ 20 ladders at r = 23 cm 1% X_0
- 16 silicon strip wafers per ladder
- Wafer is double sided silicon
 - \circ 42 mm \times 73 mm
 - 768 strips at angle of 35 mrad
 - Resolution is
 - \circ 20 μ m in $r\phi$
 - o 740 μm in z
 - Shaping time is $1.2 2 \mu s$



The SSD is needed for HFT Tracking



- Part of tracking package
- Graded resolution
- •Hit matching from the outside → in


TPC ⇒ SSD

 $IST \Rightarrow PIXEL2$

PIXEL2 ⇒ PIXEL1

PIXEL1⇒ vertex

PIXEL alone



History

- Run 4 (2003-2004) Au+Au
 - Half of the SSD installed
- Run 5 (2004-2005) Cu+Cu
 - Full detector in STAR
 - Data in analysis
- Run 6 (2006) p+p
 - SSD removed from data stream
- Run 7 (2007) Au + Au
 - SSD group reconstituted
 - In data stream
- Run 8 (2008)
 - Removed for low mass run
 - Moved to Nantes to refurbish and upgrade electronics


Current Hardware Situation

- SSD operational in Nantes
- All ladders tested
- No dead ladders
 - Ladder 7 fixed by replacing ADC and connection board
- Preparing to upgrade to DAQ1000

Recent Testing Results

- ladders (need 20)
 - • very good ladders
 - TLadders with one bad hybrid (half module)
 - •Those ladders may be fully "good" if the bias of the module is forced.
 - 9 Ladders with several bad modules
 - •Some need to have the bias forced
 - •Because of problem with JTAG chain, configuration cannot be done with present TEST software
 - •Some improvement can be done on these ladders
 - 4 with a real high voltage trip
 - •Can be very good if capacitors replaced
 - •Will result in 10 very good ladders when fixed

Summary with NO repair



Comments

- Each side of the SSD is read separately
- Really two separate detectors
- Currently STAR software requires both n side and p side for a track
 - Efficiency will improve if can allow only one side
 - Action item for STAR software


High Current on a few ladders

- Capacitors are added to isolate power lines
- High current on a few modules probably due to bad capacitor
- Should be repairable
- Locate bad capacitors by infrared imagery

Infrared scan



Leaking Capacitor





Capacitor


Developing tooling to remove bad ones

Upgrade Plan

- Keep silicon
- Upgrade the SSD readout electronics from 200 Hz to 1 kHz
- Design a new slow controls system to be compatible with the new electronics
- Ensure that all cone modifications proposed for the FGT and HFT are compatible with the re-installation of the SSD
- Redesign and replace the cooling system

Electronics upgrade

- New connection board to merge the data from modules to the ADC
- Replace ADC board with a new high speed ADC
- Read ladders in parallel
- New RDO board to collect data from 5 ladders
- Send data to a PC via a DDL fiber link
 - 160 MB/s
 - Need 8 RDOs and 8 DDL



OUR Run Plan

- Run 10 Installation during summer 2009
 - Roll out detector
 - Install SSD with three ladders (one sector) of upgraded electronics
- Run 11 Installation during summer 2010
 - Roll out detector
 - Remove prototype electronics
 - Reinstall SSD with a full set of upgraded electronics
 - Commission detector

*Assuming standard RHIC run scenario

SSD Upgrade Proposal

- Submitted proposal in the Fall
- Committee chaired by Rene
- Committee submitted report shortly after
 Quark Matter
 - Unseen by us
 - Understand favorable
 - Some homework for us

.. Status of Funding of the SSD Upgrade Proposal


In limbo - June 17, 2008

Need Commitment

- Nantes engineers are committed to the upgrade
 - Nevertheless, they have Nantes priorities
 - STAR should make an agreement with Nantes Management
- Start the engineering so that integration requirements are established
- Young scientists need to know that there is a real project
- STAR needs to make a commitment to the upgrade

Analysis of Cu-Cu and Au-Au

- Efficiency Cu- Cu good
- In data stream
- Will improve with a little work
- See talk by Jonathan Bouchet on Monday and Thursday
- Who will do Au-Au?



Summary

- SSD in physics data stream for Cu-Cu
- Need someone to finalize Au-Au analysis
- SSD silicon in good shape
- SSD ready to be brought back into STAR
- Upgrade plan to make the SSD compatible with DAQ1000 and the HFT
- Waiting for approval and funding for STAR
- Eager to join HFT upgrade
- Looking for people to join the SSD group